



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> :

H01M 12/06, 2/02

A1

(11) International Publication Number:

WO 00/36689

(43) International Publication Date:

22 June 2000 (22.06.00)

(21) International Application Number: PCT/US99/28253

(22) International Filing Date: 30 November 1999 (30.11.99)

(30) Priority Data:

60/112,292	15 December 1998 (15.12.98)	US
09/293,458	15 April 1999 (15.04.99)	US

(71) Applicant (for all designated States except US): ELECTRIC FUEL LIMITED (IL/IL); Western Industrial Park, P.O. Box 641, 99000 Bet Shemesh (IL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ABRAMSON, Mariano (IL/IL); Carmon Street 16, Jerusalem (IL). DOPP, Robert, B. (US/US); 1925 Fields Pond Glen, Marietta, GA 30068 (US). SHRIM, Yaron (IL/IL); Mazel Shor Street 20/1, Jerusalem (IL).

(74) Agent: CATAN, Mark, A.; Lyon &amp; Lyon LLP, 633 West Fifth Street, Suite 4700, Los Angeles, CA 90071-2066 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: STRUCTURE FOR A PRISM-SHAPED METAL-AIR BATTERY CELL WITH FEATURES TO PREVENT ELECTROLYTE LEAKAGE AND TO MAINTAIN CONNECTIVITY BETWEEN AN AIR CATHODE AND A CASING ELEMENT



## (57) Abstract

A prism shaped battery cell has at least two casing elements. The casing elements are mutually engageable and are assembled by bending or crimping a portion of one casing element at least partially around a second casing element. The shape of the casing elements as well as the materials of the casing elements reduce the likelihood that the casing will corrugate during the crimping process. By reducing the size of the walls of a casing element at the corner portions, the negative effects of corrugation due to crimping are reduced. The casing elements also contain features that support a generally planar electrode in a position within the battery cell so that the edge of the electrode maintains contact with a casing element.